

CAST ALUMINUM ASSEMBLY- TABLE TOPS

ITEMS INCLUDED IN THE HARDWARE KIT:

- 1 FOUR (4) STAINLESS STEEL 14 MM NUTS
- 2 FOUR (4) STAINLESSS STEEL LOCK WASHERS
- 3 FOUR (4) STAINLESS STEEL WASHERS
- 4 FOUR (4) STAINLESS STEEL ALL -THREAD HEADLESS BOLTS WITH SLOTTED END

PARTS INCLUDED:

- 1 ONE (1) CAST ALUMINUM TABLE TOP

TOOLS REQUIRED:

- 1 MANUAL OR ELECTRIC FLAT -HEAD SCREWDRIVER
- 2 SOCKET WRENCH WITH 14 MM SOCKET

STEP 1:

PLACE THE TABLE TOP ON A PADDED SURFACE WITH BOTTOM FACING UPWARD. PLACE THE FOUR HEADLESS BOLTS INTO THE FOUR HOLES ON THE BOTTOM OF THE TOP, WITH THE SLOTTED END FACING UPWARD. TIGHTEN USING A FLAT --HEAD SCREWDRIVER.

STEP 2:

TURN THE ASSEMBLED TABLE BASE (SEE SEPARATE ASSEMBLY INSTRUCTIONS FOR BASE) UPSIDE-DOWN AND PLACE THE BASE ON TOP OF THE TABLE TOP BOTTOM, INSERTING THE TABLE BASE HOLES INTO THE BOLTS PROTRUDING FROM THE TOP. SEE ILLUSTRATION.

STEP 3:

PLACE A WASHER, LOCKING WASHER AND THEN NUT ON EACH BOLT, AS SHOWN. **HAND TIGHTEN ONLY.**

STEP 4:

TIGHTEN NUTS SECURING BASE LEGS TO STRETCHERS FIRST, THEN TIGHTEN NUTS SECURING TOP TO BASE. **DO NOT OVER-TIGHTEN. DO NOT USE ELECTRIC DRILL.**

